

WATERMAKER

REVERSE OSMOSIS WATERMAKER

H2Ocean Watermaker Premium series is a **FULL AUTOMATIC** system consisting of 5 different models ranging from 90 liters per hour to 240 liters of water production capacity with high efficiency and easy to use system. There is an automatic washing / cleaning function that switches itself after each use. Produces sterile water and works with remote control.



AUTOMATIC WASHING / CLEANING FUNCTION AFTER EACH USE (PRIMING)

mHI 240



UV FILTER

mHI 120



REMOTE CONTROL PANEL



Unlike other watermaker, H2Ocean Automatic Washing System only use its own sterile water. So that the membranes are protected and you can keep the device without running up to 4 weeks. There is a digital remote control panel on system for easy to use. With this panel, the watermaker can be turned on and off without going into engine room.

- Corrosion-resistant stainless steel case with 316-L quality
- Possibility of modular installation in boats with space problem
- Dow Chemical high technologie membrans
- Atlas Filtri (5M-25M) 2 stage pre-filtering system
- 316-L quality stainless steel low pressure pump
- Membrane protection system against sudden pressure rises

mHL 120

- · High pressure protection system against sea water failure
- 2 years warranty

nPS90

MODEL

		pilozo	PILLIZO	PILLIOU	PILLATO	
Fresh Water Production	Liter/Hrs	90,00	120,00	180,00	240,00	
	US Galoon/Hrs	23,80	31,70	47,55	63,40	
	Liter/Day	2160	2880	4320	5760	
	US Galoon/Day	571,4	760,8	1141,2	1521,6	
Technical Specification	Power (kW) Start/Continuous	2,2/2,0	2,2/2,0	2,2/2,0	2,2/2,0	
	Voltage (V)	220	220	220	220	
	Weight (Kg)	77	81	92	97	
	Dimensions (cm)	100 x 48 x 44	108 x 48 x 44	108 x 48 x 44	108 x 48 x 44	
	Sound level /1m	55	53	50	50	





H2Ocean Watermaker Eco series is a MANUEL system consisting of 5 different models ranging from 90 liters per hour to 240 liters of water production capacity with high efficiency and easy to use system. Long life thermoplastic case ECO model devices do not have UV sterilizer, digital remote control panel and automatic washing system. If request they can be add as an option.

- Long life thermoplastic case
- Corrosion-resistant stainless steel membran tubes with 316-L quality
- Possibility of modular installation in boats with space problem
- Dow Chemical high technologie membrans
- Atlas Filtri (5M-25M) 2 stage pre-filtering system
- 316-L quality stainless steel low pressure pump
- Membrane protection system against sudden pressure rises
- High pressure protection system against sea water failure
- 1 year warranty

MODEL	eHS90	eHL120	eHL180	eHL240
Liter/Hrs	90,00	120,00	180,00	240,00
US Galoon/Hrs	23,80	31,70	47,55	63,40
Liter/Day	2160	2880	4320	5760
US Galoon/Day	571,4	760,8	1141,2	1521,6
Power (kW) Start/Continuous	2,2/2,0	2,2/2,0	2,2/2,0	2,2/2,0
Voltage (V)	220	220	220	220
Weight (Kg)	73	77	82	92
Dimensions (cm)	100 x 48 x 44	108 x 48 x 44	108 x 48 x 44	108 x 48 x 44
Sound level /1m	55	53	50	50

Mrk: Yalı Mahallesi İçmeler No:69 Bodrum / Muğla - TÜRKİYE T. +90 252 316 00 63 F. +90 252 316 0163 info@giayachting.com GIA Marine Shop: Aydıntepe Mah. Sahilyolu Cad. Alize İş Merkezi No:191/32 Tuzla / İstanbul - TÜRKİYE T. +90 216 494 1060 F. +90 216 494 1066 tuzla@giayachting.com

Sertifikalıdır

Certificated



www.giayachting.com